



SPECIFICATIONS:

DESCRIPTION

Wall-mounted sconces featuring handcrafted glasses. 9" sq. model (#8884) and 5" wide model (#8886) are **ADA-compliant**.

LAMPING

Standard: 60W or 75W A19 120V incandescent, suitable for dimming.

CFL: 18W 4-Pin CFL with non-dimming electronic ballast. 120V, lamp not included.

LED: 7W LED Replaceable source 120V, non-dimmable, included.

DIFFUSER

Diffuser shall be handcrafted Opal Matte glass.

CONSTRUCTION

Stamped aluminum fitter is powder coated white. Glass is secured by stainless steel set screws.


MOUNTING

Installs directly to a 4" octagonal outlet box. 75°C supply wire required for incandescent lamping. Centered on fixture, except 8886- fixture centerline is positioned 0.75" below box centerline.

LABELS


UL or ETL Listed. Suitable for Wet Locations (interior or exterior use).

Geo 5: #8886




FIXTURE	LAMP OPTIONS
888607 8.5" H Opal Matte	(blank) 1x 60W A19 Incan D1 1x 13W Quad 120V LED 1x 7W LED 120V, non-dimmable

Geo 9: #8884



FIXTURE	LAMP OPTIONS
888307 9" H Opal Matte	(blank) 1x 60W A19 Incan D1 1x 13W Quad 120V F1 1x 18W TBX 120V LED 1x 7W LED 120V, non-dimmable

Geo 11: #8883



FIXTURE	LAMP OPTIONS
888307 11.0" H Opal Matte	(blank) 2x 60W A19 Incan E2 2x 18W Quad 120V K1 1x 32W TBX 120V LED 2x 7W LED 120V, non-dimmable

Ex. 888307
2 Lt. Geo 11 Sconce w/ Opal Matte Glass, White Finish

Project Information:

Blank box for project information.



GEO SHOWN IN OPAL MATTE

888607
OPAL MATTE



LED SCONCES:

- Total power of only 7 watts
- Non-dimmable
- Rated life: 30,000 hours
- 500 lumens
- CCT: 3000° Kelvin
- CRI: 80+

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.