



PRISMO 10 / 16

SCONCES OUTDOOR

location:
WET

SPECIFICATIONS:

DESCRIPTION

Wall-mounted sconce featuring handcrafted frosted glass.

LAMPING

Standard: 60W A19 120V incandescent, suitable for dimming.

CFL: 18W 4-Pin CFL with non-dimming electronic ballast. 120V, lamp not included.

LED: 7W LED Replaceable source 120V, non-dimmable, included.

DIFFUSER

Wall-mounted sconce featuring handcrafted frosted glass.

CONSTRUCTION

Stamped aluminum fitter is powder coated white.

Glass is secured by stainless steel set screws.

Prismo 10 fitter is 4.125" W x 7.375" H x 0.75" D

Prismo 16 fitter is 4.125" W x 12" H x 0.8" D


MOUNTING

Installs directly to a 4" octagonal outlet box. 75°C supply wire required for incandescent lamping. Fixture is centered on the outlet box. 10' fixture centerline is 0.75" below box centerline. Orient horizontal or vertical, wall-mount only.


LABELS

UL or ETL Listed. Suitable for Wet Locations (interior or exterior use).

Prismo 10: #3045



Prismo 16: #3046



PRISMO 16 & PRISMO 10 SHOWN IN FROST/CLEAR

ORDERING:

FIXTURE	LAMP OPTIONS	FIXTURE	LAMP OPTIONS
304504 10.5" H Frost/Clear	(blank) 1x 60W A19 Incan E1 1x 18W Quad 120V LED 1x 7W LED 120V, non-dimmable	304604 16" H Frost/Clear	(blank) 2x 60W A19 Incan H1 1x 26W Quad 120V LED 2x 7W LED 120V, non-dimmable

Ex. 304604

2 Lt. Prismo 16 Sconce w/ Frost/Clear Glass,
White Finish

Project Information:

Empty box for project information.

LED SCONCES:

- Total power of only 7 watts
- Non-dimmable
- Rated life: 30,000 hours
- 500 lumens
- CCT: 3000° Kelvin
- CRI: 80+

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.