

Product Specifications for E94472-24		
Job Name:	Job Type:	
	51	
Quantity:	Comments	



E94472-24

Starburst 1-Light RapidJack Pendant and Canopy

Finish	Glass/Shade	Product Category
	Clear	Mini Pendant

Lamping		Measurements
Number of Bulb(s)	1	Width
Light Type	Xenon	Height
Bulb Type	12V G4	Length
Max Bulb Wattage	20	Extension
Max Fixture Wattage	20	Back Plate Wi
Rated Life	±2,000 Hours	Back Plate He
Rated Lumens	±320	HCO
Color Temp	±2,900 K	Min Overall He
Bulb(s) Included	Yes	Max Overall H
Light Up/Down	N/A	Hanging Weig
Beam Spread	N/A	Height Adjusta
CRI	N/A	Slope
Photo Cell Included	N/A	Chain Length
Ballast/Driver/Transformer	No	Wire Length
Dimmable	Low Voltage	Canopy Width
		Canopy Heigh

weasurements	
Width	4.00"
Height	4.00"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
НСО	N/A
Min Overall Height	N/A
Max Overall Height	126.00"
Hanging Weight	2.26 lb(s)
Height Adjustable	Yes
Slope	N/A
Chain Length	N/A
Wire Length	72.00"
Canopy Width	4.5"
Canopy Height	1.0"
Canopy Length	

Shipping	
Carton Weight	3.75 lb(s)
Carton Width	11.00"
Carton Height	11.00"
Carton Length	11.00"
Carton Cubic Feet	N/A
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes
-	

Certification	Other	Equivalents

Safety Rating	Dry	UPC Code
Energy Star	No	Material
CA Title 24	No	
CA Title 20	No	
ADA	No	

845094053897	Incandescent Watts	N/A
N/A	Fluorescent Watts	N/A

ET2 Contemporary Lighting and all designs, logos and images © 2014 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.