



15073 AZT



15074 AZT

BRICK LIGHT

Designed to be integrated into brick walls during construction. Casts a low, even spread of light. Available with or without louvers.

SPECIFICATIONS

Housing Die-cast aluminum with a fully sealed heat-resistant glass lens

Finish Textured Architectural Bronze


Wiring Wire connection must be made inside junction box. 12-Volt bi-pin, high temperature porcelain socket.

Light Bulb (2) 10-W. Max. Q10T3 (15571CLR) halogen (nominal at 12-Volts) supplied. 75° supply wire required.

Masonry or Concrete use only



15073
Louver face



15074
Heat-resistant glass lens

15073 – Footcandles/Distance from Fixture Center

| Mounting Height | .5' | 1' | 1.5' | 2' | 2.5' | 3' | 3.5' | 4' | 4.5' | 5' |
|-----------------|-----|-----|------|----|------|-----|------|-----|------|-----|
| 12" | .3 | 1.1 | .8 | .5 | .1 | .02 | - | - | - | - |
| 24" | - | - | .1 | .2 | .2 | .1 | .03 | .02 | - | - |
| 36" | - | - | - | - | .01 | .01 | .03 | .06 | .03 | .01 |

15074 – Footcandles/Distance from Fixture Center

| Mounting Height | .5' | 1' | 1.5' | 2' | 2.5' | 3' | 3.5' | 4' |
|-----------------|-----|-----|------|-----|------|-----|------|-----|
| 12" | - | - | - | - | .01 | .04 | .04 | - |
| 24" | - | - | .06 | .1 | .09 | .04 | .04 | - |
| 36" | - | .02 | .04 | .04 | .04 | .04 | .04 | .01 |