



15211 MST



15211 AZT



15211 BKT

Versatile fixture with wider light distribution for paths and low areas of groundcover. Stem or bollard, ordered separately.

SPECIFICATIONS

Housing Durable die-cast aluminum construction. High impact resistant diffuser. *Mounting stems and bollard kits sold separately.*

Finish Textured Architectural Bronze, Textured Black, Textured Midnight Spruce™

Wiring 30" of usable 105°C 18 AWG wire leads. 120-Volt, medium base porcelain socket with nickel plated screw shell.

Lamp Type 75-W. Max. A19 light bulb (not supplied)

Optional Mounting Accessories

15656, 15657 or 15658 – Stems

15276 – Power Post®

15665, 15666 or 15667 – Bollard

15578 – Bollard Mounting Stakes

15671 – Bollard Template Kit

15601 – Surface Mounting Flange

(for attachment to junction box, not included)

15602 – Flange Mounting Nipple



Mounting stems



Bollard kits



U.S. Patent No. Des. 330,603

Canada Patent No. 69176

Korea Design Registration Number 126685

Footcandles/Distance from Fixture Center

Stem Height	1'	2'	3'	4'	5'	6'	7'	8'	9'
12"	27.1	11.7	2.8	1.2	.89	.34	.18	.07	-
*18"	19	9.5	4.6	1.7	.82	.45	.31	.18	.07
24"	14.6	7.8	4.8	2.4	1	.55	.27	.27	.14