



15383 AZT



15383 BR

15383 BBR

75-WATT HALOGEN BI-PIN ACCENT LIGHT

The clarity of halogen in a larger (4½" diameter) size for wider light spread.

SPECIFICATIONS

Housing Durable die-cast aluminum construction (BR and BBR versions are die-cast brass). Heat-resistant flat glass fully sealed for above horizon outdoor usage.

Finish Textured Architectural Bronze, Brass, Bronzed Brass

Wiring 38" of usable #18-2, SPT-1-W leads. Cable connector supplied with fixture. 12-Volt bi-pin high temperature porcelain socket.

Light Bulb 75-W Max. (BR and BBR 20-W. Max. Canada) Q50T4 (15550CLR) halogen (nominal at 12-Volts) supplied

Mounting Accessories Included

8" In-ground stake


Optional Mounting Accessories

15656, 15657, 15658 or 15570 – Stems

15649 – Stem Coupler

15601 – Surface Mounting Flange

15607 – Tree/Surface Mounting Bracket



15383

Footcandles/Distance from Fixture Center

A-Aiming Angle	0°			30°			45°			
	D	FC	L	W	FC	L	W	FC	L	W
5'	8.76	4.45	4.45	5.69	6.36	5.14	3.1	11.11	6.3	
10'	2.19	8.9	8.9	1.42	12.71	10.28	.77	22.21	12.59	
20'	.55	17.81	17.81	.36	25.43	20.56	.19	44.42	25.19	