



15385 BE

HOODED ADJUSTABLE WIDE FLOOD LIGHT

Large floodlight with wide beam spread for dramatic wall-washing of taller walls and vertical stonework. Eyebrow shields glare to allow for horizontal use.

SPECIFICATIONS

Housing Durable die-cast aluminum construction (BR and BBR versions are die-cast brass). Heat-resistant flat glass lens is fully sealed for outdoor usage.

Finish Textured Architectural Bronze, Beach, Brass, Bronzed Brass

Wiring 35" of usable #18-2, SPT-1-W leads. Cable connector supplied with fixture. 12-Volt bi-pin, high temperature porcelain socket.

Light Bulb Alum 75-W. Max. Brass. 50-W. Max. 50-W. QT3 or QT4 (15550CLR) (nominal at 12-Volts) supplied.

Mounting Accessories Included

8" In-ground stake

Optional Mounting Accessories

15601 – Surface Mounting Flange

15607 – Tree/Surface Mounting Bracket

15656, 15657, 15658 – Stems

15649 – Stem Coupler

Bulk Pack

15385AZT6 – Bulk Pack includes 8" ground stakes

U.S. Patent Pending

Vertical Illuminance (FC)

Mounting Distance from Surface	A	B	C	D	E	F
3'	9.30	5.43	1.81	.9	.18	.09
4'	5.08	3.05	1.01	.51	.10	.05
5'	3.25	1.95	.65	.33	.07	.03
6'	2.26	1.35	.45	.23	.05	.02
7'	1.66	.99	.33	.17	.03	.03
8'	1.27	.76	.25	.13	.03	.01
9'	1	.6	.2	.1	.02	.01
10'	.81	.49	.16	.08	.02	.01



15385 AZT



15385 BBR



15385 BR

