

Job Name:		Item Number:	
Specifier Name:		Sales Agency:	
Specifier Contact:		Agency Contact:	
Fixture Type:		Comments:	
Quantity:		Approval:	

120w 12V (2 x 60w) Dual Output Hardwire Electronic Transformer



Description

UL 2108, electrically isolated 5VA flame resistant plastic enclosure. Includes terminal block for one 10/2 AWG max. (i.e. Romex) input and two Class II 60w outputs for 10/2 AWG Ambiance Lx cable. Ambiance electronic transformers have soft start circuitry which increases lamp life. They emit no audible noise, are UL and C-UL approved, moisture and shock resistant, employ automatically resetting short circuit protection, and are dimmable using an electronic low-voltage (ELV) dimmer.

Specifications

Item Number	98176-12
Finish	Black
Dimensions	L: 5" W: 3 1/4" H: 1"
Mounting Proc.	Screw(s)
Safety Listing	UL Listed for Dry Locations cUL Listed for Dry Locations
Warranty	1-Year Warranty

Instruction Sheets

- Trilingual (English, Spanish, and French) (HC-971FS)

Shipping Information:

Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	UPS Ship
Individual	98176-12	1	785652034763	6	3.25	1.25	0.014	0.5	Yes
Master Pack	98176-12	10	10785652034760	7.75	7.75	7.25	0.252	5.9	Yes
Shipping Master		40							